



# Tapiflex TX 243/244

## DESCRIPTION

Printed acoustic vinyl floorcovering with high density foam backing on a glass fibre stabilized carrier, filler free wear layer.

PUR Reinforced, built-in fungistatic & bacteriostatic Sanitized® treatment. Product standard: EN 651.

Technical data	Standards	TX 243 sheet	TX 244 sheet	TX 243 tile	TX 244 tile
Classification	EN 685 domestic commercial industrial UPEC	Classes: 33 42 U3 P3 E2/3 C2	Classes: 34 U4 P3 E2/3 C2	Classes: 33 42 U3 P3 E2/3 C2	Classes: 34 U4 P3 E2/3 C2
Total thickness	EN 428	3.15 mm	3.30 mm	3.10 mm	3.25 mm
Wear layer thickness	EN 429	0.50 mm	0.65 mm	0.50 mm	0.65 mm
Total weight	EN 430	3 060 g/m <sup>2</sup>	3 255 g/m <sup>2</sup>	3 190 g/m <sup>2</sup>	3 385 g/m <sup>2</sup>
PUR Reinforcement		Yes	Yes	Yes	Yes
Abrasion Group	EN 660-1	Group T: ≤ 0.08 mm			
Residual indentation	EN 433	0.17 mm			
Underfoot comfort	EN 433	≥ 0.40 mm			
Furniture leg	EN 424	No damage			
Castor chair	EN 425	No damage			
Dimensional stability	EN 434	≤ 0.10 %			
Curl resultant to heat	EN 434	≤ 8 mm	≤ 8 mm	≤ 2 mm	≤ 2 mm
Reaction to fire	EN 13501-1 NF P 92506 ASTM E648	C <sub>fl</sub> s1 M3 Category 1			
Slip resistance	DIN 51130 pr EN 13893	R10 ≥ 0.3			
Electrostatic properties	EN 1815 EN 1081 EN 14041	2 kV R1 > 10 <sup>10</sup> Ω Antistatic			
Impact sound reduction	EN ISO 140-8 EN ISO 717/2 ΔL <sub>w</sub>	19 dB	19 dB	18 dB	18 dB
Acoustic improvement	NF S 31-074 L <sub>n,e,w</sub>	61 dB			
Light fastness	EN ISO 105-B02	≥ 6/8			
Chemical resistance	EN 423	High resistance			
Resistance to bacteria	NF EN ISO 846	Sanitized - Grade 0 - high fungi effect			
Thermal resistance Underfloor heating	EN 12524	0.05 m <sup>2</sup> K/W Suitable			
Colours		Saphyr: 13 Corail: 15		Saphyr: 8	
Form of delivery	EN 426 EN 427	Rolls: 23 lm x 2 m		Tiles: 0.50 m x 0.50 m	

The above information is subject to modification for the benefit of further improvement (05/06). For more detailed technical information, please contact Tarkett. Follow Tarkett's installation and maintenance instructions carefully. These instructions are available upon request.



TARKETT SALES COMPANIES

www.tarkett-commercial.com

> **Australia:** Tarkett Australia Pty Ltd – Tel. +61 2 96 34 73 73 > **Austria:** Tarkett AG Niederlassung Wien – Tel. +43 1 47 88 062 > **Baltic States:** Tarkett SAS – Tel. +370 37 262 220  
 > **Belgium:** S.A. Tarkett NV – Tel. +32 2 520 04 67 > **China:** Tarkett Asia Pacific Limited Shanghai Representative Office – Tel. +86 (21) 62 88 15 38 > **Czech Republic:** Tarkett SAS, org. slozka - Tel. +420-271 001 602 > **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11 > **Finland:** Tarkett Oy – Tel. +358 9 5406 5870 > **France:** Tarkett SAS – Tel. +33 1 41 20 42 49  
 > **Germany:** Tarkett AG, Bereich Objekt – Tel. +49 6233 810 > **Greece:** Tarkett Monoprosopi Ltd – Tel. +30 2 10 576 3889 > **Hong Kong:** Tarkett Asia Pacific Ltd. – Tel. +852 2511 8716 > **Hungary:** Tarkett SAS – Tel. +36 1 437-8150 > **Italy:** Tarkett S.p.A. – Tel. +39 02 893 411 > **Luxembourg:** Tel. +352 949 211 8804 > **Middle East:** Tarkett Middle East – Tel. +961 1 75 2363/4 > **Netherlands:** Tarkett Benelux B.V. – Tel. +31 76 57 80 760 > **Norway:** Tarkett AS – Tel. +47 32 20 92 00 > **Poland:** Tarkett Sp. z o.o. – Tel. +48 22 598 08 81  
 > **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 > **Russian Federation:** Tarkett Russia – Tel. +7 4 95 777 69 83 > **Slovakia:** Tarkett SAS – Tel. +421 37 6515 404 > **Singapore:** Tarkett Far East – Tel. +65 6743 53 84 > **South East Europe:** Tarkett Trade d.o.o. – Tel. +381 21 7557 649 • (44) 569 12 21 > **United Kingdom:** Tarkett-Marley Floors Limited – Tel. +44 (0) 1622 854 040 > **Spain:** Tarkett Floors S.L. – Tel. +34 91 358 00 35 > **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 > **Switzerland:** Tarkett AG, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 > **Ukraine:** Tarkett UA – Tel. +380380 (44) 569 12 21 > **USA/Canada:** Tarkett Inc. USA – Tel. +1 713 869 5811 • Johnsonite – Tel. +1 440 543 8916 > **Tarkett International:** Tel. +49 6233 811 755 – Tel. +33 41 20 41 01